



**1012 E.B.C.™ Three Warmer
In-Line Automatic Coffee Brewer**
(with Hot Water Faucet)

**1016 E.B.C. Three Warmer
In-Line Automatic Coffee Brewer**
(with Hot Water Faucet)

**1040 E.B.C. Two Warmer
In-Line Automatic Coffee Brewer**
(with Hot Water Faucet)

**1072 E.B.C. Three Warmer Stepped
Right Automatic Coffee Brewer**
(with Hot Water Faucet)



Features

- After Hours Mode will automatically reduce water temperature when not in use, saving energy and increasing component life.
- Precise brewing temperature is established and maintained throughout the brew cycle, providing cold brew lockout and ensuring full flavored coffee and faster brewer recovery.
- Countdown Quality Timer™ will signal the end of preset coffee holding time.
- Brew cycle timer eliminates the risk of double brewing during brew cycle.
- A high level of commonality of parts with other Bloomfield models will significantly reduce the inventory of spare parts required to service many body styles.
- Exclusive design provides easy access to components for quick service.
- Ready-to-Brew light indicates the proper water temperature to help eliminate the guesswork in brewing.
- Built in pour over feature provides flexibility.
- Unique water valve with built-in flow control assures consistent operation at 20-80 p.s.i.



- Electronic sensor recognizes water temperature extremely accurately for more consistent product.
- Superior sprayhead design spreads water over the coffee grounds, creating agitation and a floating action that completely saturates the coffee to capture the full, rich essence.



Specifications

| MODELS | WATTS | VOLTS | AMPS | POWER SUPPLY CORD | DIMENSIONS |
|--------|-------|------------------|------|-------------------|----------------------------|
| 1012 | 1800 | 120 | 1.5 | NEMA 5-15P | 21"D x 8.5/8"W x 18.7/8"H |
| 1016 | 3800 | 115/230 0-4 WIRE | 1.7 | NONE | 21"D x 8.5/8"W x 18.7/8"H |
| 1040 | 1700 | 120 | 1.4 | NEMA 5-15P | 17"D x 8.5/4"W x 16.7/8"H |
| 1072 | 1800 | 120 | 1.5 | NEMA 5-15P | 17"D x 16.1/4"W x 16.7/8"H |
| 1012CA | 1500 | 120 | 12.5 | NEMA 5-15P | 21"D x 8.5/8"W x 18.7/8"H |
| 1040CA | 1500 | 120 | 12.5 | NEMA 5-15P | 17"D x 8.5/4"W x 16.7/8"H |
| 1072CA | 1500 | 120 | 12.5 | NEMA 5-15P | 17"D x 16.1/4"W x 16.7/8"H |

1012CA, 1040CA, 1072CA: Use the standard standard.

NOTE: Specifications are subject to change without notice and are not intended for installation purposes. See operation and maintenance manual for complete instructions.